

AGRIMAX RT 945 - Technical Specifications



Description

AGRIMAX RT 945 is specially designed for row crops: it does not damage the crops and preserves the yield. Excellent self-cleaning features allow for a quick change from field operations to road usage, where AGRIMAX RT 945 shows brilliant performance. Its strong carcass gives the tire excellent stability, outstanding traction, and exceptional durability.

UM

International Standard

Construction

 RADIAL

Machinery

Agriculture: Sprayer • Tractor

Version	STANDARD
Type	TL
Tyre Size	320/90 R 46 (12.4 R 46)
LI/SS	148 D/151 A8

Dimensions International Standard

Section Width (mm)	319
Overall Diameter (mm)	1744
Static Loaded Radius (mm)	810
Rolling Circumference (mm)	5232
SRI (mm)	825
Rim Rec	W 10
Rim Alt	W 9 ; W 11
ECE	E11-106R-004068
TRA Code	R1W

Load capacity (Kg)

km/h / bar	0.8	1.2	1.6	2.0	2.4	2.8	3.2	3.6
65	1355	1765	2145	2365	2490	2745	2965	3150
50	1425	1855	2255	2485	2615	2880	3115	3310
40	1485	1935	2350	2590	2730	3005	3245	3450
30	1560	2030	2465	2715	2860	3150	3405	3620
10	2035	2650	3215	3545	3735	4115	4445	4725

Printed on 21/04/2024 00:20

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..