

AGRIMAX RT 955 - Technical Specifications



Description

AGRIMAX RT 955 is a BKT radial tire for row crop applications, while some sizes are also suitable for spraying and vineyards. The special tread design with a rounded shoulder provides excellent traction performance, stability and self-cleaning properties. Thanks to its strong casing, AGRIMAX RT 955 has a high load capacity.

UM

International Standard

Construction

 RADIAL

Machinery

Agriculture: Sprayer • Vineyard Harvester

Version	STANDARD
Type	TL
Tyre Size	270/95 R 32 (11.2 R 32)
LI/SS	136 A8/B

Dimensions International Standard

Section Width (mm)	275
Overall Diameter (mm)	1327
Static Loaded Radius (mm)	614
Rolling Circumference (mm)	4076
SRI (mm)	625
Rim Rec	W 9
Rim Alt	W 8 ; W 10
ECE	E4-106R-000776
TRA Code	R1

Load capacity (Kg)

km/h / bar	0.8	1.2	1.6	2.0	2.4	2.8	3.2	3.6	4.0	4.4
50	875	1145	1390	1525	1615	1770	1930	2085	2240	-
40	875	1145	1390	1525	1615	1770	1930	2085	2240	-
30	940	1225	1490	1635	1730	1900	2065	2235	2400	-
10	1045	1315	1615	1920	2220	2285	2555	2825	3095	3360

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.

Printed on 01/05/2025 03:15

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..