

## AGRIMAX RT 955 - Technical Specifications



### Description

AGRIMAX RT 955 is a BKT radial tire for row crop applications, while some sizes are also suitable for spraying and vineyards. The special tread design with a rounded shoulder provides excellent traction performance, stability and self-cleaning properties. Thanks to its strong casing, AGRIMAX RT 955 has a high load capacity.

### UM

International Standard

### Construction

 RADIAL

### Machinery

Agriculture: Sprayer • Vineyard Harvester

Version	STANDARD
Type	TL
Tyre Size	270/95 R 46 (11.2 R 46)
LI/SS	143 A8/B

## Dimensions International Standard

Section Width (mm)	275
Overall Diameter (mm)	1683
Static Loaded Radius (mm)	792
Rolling Circumference (mm)	5169
SRI (mm)	800
Rim Rec	W 9
Rim Alt	W 8 ; W 10
ECE	E4-106R-000785
TRA Code	R1

## Load capacity (Kg)

km/h / bar	0.8	1.2	1.6	2.0	2.4	2.8	3.2	3.6	4.0	4.4
50	1120	1445	1745	1910	2045	2235	2430	2590	2725	-
40	1120	1445	1745	1910	2045	2235	2430	2590	2725	-
30	1200	1550	1870	2045	2190	2395	2600	2775	2920	-
10	1545	2000	2410	2640	2825	3090	3355	3580	3765	4090

Printed on 26/04/2024 19:07

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..