

AGRIMAX RT 955 - Technical Specifications



Description

AGRIMAX RT 955 is a BKT radial tire for row crop applications, while some sizes are also suitable for spraying and vineyards. The special tread design with a rounded shoulder provides excellent traction performance, stability and self-cleaning properties. Thanks to its strong casing, AGRIMAX RT 955 has a high load capacity.

UM

International Standard

Construction

 RADIAL

Machinery

Agriculture: Sprayer • Vineyard Harvester

| | |
|-----------|----------------------------|
| Version | STANDARD |
| Type | TL |
| Tyre Size | 340/85 R 46 (13.6 R 46) |
| LI/SS | 150 A8/B |

Dimensions International Standard

| | |
|----------------------------|----------------|
| Section Width (mm) | 353 |
| Overall Diameter (mm) | 1746 |
| Static Loaded Radius (mm) | 826 |
| Rolling Circumference (mm) | 5346 |
| SRI (mm) | 850 |
| Rim Rec | W 12 |
| Rim Alt | W 11 |
| ECE | E4-106R-001828 |
| TRA Code | R1 |

Load capacity (Kg)

| km/h / bar | 0.8 | 1.2 | 1.6 | 2.0 | 2.4 | 2.8 | 3.2 | 3.6 | 4.0 |
|------------|------|------|------|------|------|------|------|------|------|
| 50 | 1445 | 1880 | 2280 | 2480 | 2650 | 2915 | 3150 | 3350 | - |
| 40 | 1445 | 1880 | 2280 | 2480 | 2650 | 2915 | 3150 | 3350 | - |
| 30 | 1545 | 2010 | 2440 | 2655 | 2835 | 3120 | 3370 | 3585 | - |
| 10 | 2065 | 2665 | 3220 | 3520 | 3770 | 4125 | 4475 | 4775 | 5025 |

Printed on 26/04/2024 18:01

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..