

AGRIMAX SPARGO - Technical Specifications



Description

AGRIMAX SPARGO is the special BKT tire for row crop applications. It has been designed for enhanced productivity in the fields and for preserving the soil in the long term. Thanks to VF technology, the tire provides higher load capacity at standard pressure. Thanks to a strong casing and an increased number of lugs, AGRIMAX SPARGO ensures outstanding durability along with strong stability both in the fields and during road transfers.

UM

International Standard

Construction

 RADIAL

Machinery

Agriculture: Sprayer

Version	STANDARD
Type	TL
Tyre Size	VF 320/90 R 54 CFO
LI/SS	168 D

Dimensions International Standard

Section Width (mm)	323
Overall Diameter (mm)	1948
Static Loaded Radius (mm)	910
Rolling Circumference (mm)	5946
SRI (mm)	925
Rim Rec	W 11
Rim Alt	W 10 ; DW 10 ; W 10 L ; DW 11
ECE	E11-106R-009070
TRA Code	R1

Load capacity (Kg)

km/h / bar	1.0	1.2	1.4	1.6	1.8	2.0	2.2	2.4	2.6	2.8	3.0	3.2	3.4	3.6	3.8	4.0	4.2	4.4
70	2230	2490	2800	3060	3215	3370	3475	3575	3760	3940	4095	4250	4380	4510	4640	4770	4975	5180
From 65 to 40	2410	2690	3025	3305	3475	3640	3755	3865	4060	4260	4425	4595	4735	4875	5015	5155	5380	5600
30	2460	2745	3090	3375	3545	3715	3830	3945	4145	4345	4515	4690	4830	4975	5115	5260	5490	5715
20	2505	2800	3150	3440	3615	3790	3905	4020	4225	4430	4605	4780	4925	5070	5215	5360	5595	5825
10	2650	2960	3330	3635	3820	4005	4130	4255	4470	4685	4870	5055	5210	5360	5515	5670	5915	6160

Printed on 05/05/2024 04:30

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..