

## AGRIMAX TURF RT 333 - Technical Specifications



### Description

AGRIMAX TURF RT 333 (R-3+) is a radial tire designed for small tractors in gardening, vineyards and orchards applications. Its rounded shoulder design provides low soil compaction and makes it extremely delicate on the ground. Its unique extra-deep tread (R-3+) and the special design with directional blocks stand for excellent traction both in the field and on the road, and an extended tire life cycle. AGRIMAX TURF RT 333 (R-3+) ensures great self-cleaning properties and thanks to its low rolling resistance, allows for significant fuel saving.

### UM

US Standard

### Construction



RADIAL

### Machinery

Agriculture: Orchard Harvester • Small Tractor • Vineyard Harvester

Version	STANDARD
Type	TL
Tyre Size	220/55 R12
LI/SS	82 A8/B

Dimensions US Standard

Usa code	94070237
Section Width (inch)	8.7
Overall Diameter (inch)	21.7
Static Loaded Radius (inch)	9.8
Rolling Circumference (inch)	64.8
Rim Rec	7
ECE	E11-106R-007600

Load capacity (lbs)

mph / psi	9	12	15	17	20	23	29	35
30	500	590	670	740	820	880	990	1050
25	500	590	670	740	820	880	990	1050
20	530	630	720	800	880	940	1050	1130
5 LT	680	790	900	1000	1100	1180	1330	1420
5 HT	530	630	720	800	880	940	1050	1130

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.

Printed on 01/05/2025 06:30

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..