

# AGRIMAX V-FLECTO - Technical Specifications



## Description

AGRIMAX V-FLECTO is BKT's response to the challenging demand of both technology and performance for high-power tractors. This tire is perfect for soil tillage and haulage applications thanks to reduced soil compaction and self-cleaning properties. With the exclusive VF technology, AGRIMAX V-FLECTO can carry heavy loads with a lower inflating pressure compared to standard and IF tires, reaching high speeds. It also features the Narrow Rim Option that allows mounting standard rims on the tire. BKT has designed this tire with optimized geometry to enhance driving comfort both in the fields and on the road reducing fuel consumption.

## UM

US Standard

## Construction

 RADIAL

## Machinery

Agriculture: High-Power Tractor

Version	STANDARD
Type	TL
Tyre Size	VF 710/75 R 38
LI/SS	183 D

## Dimensions US Standard

Usa code	94066339
Section Width (inch)	28.3
Overall Diameter (inch)	81.1
Static Loaded Radius (inch)	35.6
Rolling Circumference (inch)	242.2
Rim Rec	DW 24 B
Rim Alt	DW 23 B ; DW 25 B
ECE	E11-106R-006764
TRA Code	R1W

## Load capacity (lbs)

mph / psi	9	12	15	17	20	23	29
45	8770	10170	11580	13150	14560	15960	17550
From 40 to 25	9640	11190	12730	14460	16000	17550	19290
20	9830	11410	12980	14750	16320	17890	19680
12	10030	11630	13240	15030	16640	18240	20060
5	10600	12300	14000	15910	17600	19300	21220
*Upto 5 Cyc with front loader	13500	15660	17820	20240	22400	24560	27010
5 HT	9830	11410	12980	14750	16320	17890	19680

\* \*For Upto 10 Cyc with front loader application inflation pressure to be increased by 0.8 bar.

Printed on 20/04/2024 12:11

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..