

AIROMAX AM 543 - Technical Specifications



Description

AIROMAX AM 543 is the ideal tire for construction applications with cranes. It shows outstanding traction and high stability. As crane tires are subject to particular stress and extreme usage conditions, AIROMAX AM 543 has been designed for providing excellent heat resistance. Besides, it is suitable for all operations requiring a high level of handling.

UM

International Standard

Construction

 RADIAL

Machinery

Industrial: Mobile Crane

| | |
|-----------|-----------------------------|
| Version | STANDARD |
| Type | TT |
| Tyre Size | 385/95 R 24 (14.00 R 24) |
| LI/SS | 170 E |

Dimensions International Standard

| | |
|----------------------------|--------|
| Overall Width (mm) | 375 |
| Overall Diameter (mm) | 1355 |
| Static Loaded Radius (mm) | 627 |
| Rolling Circumference (mm) | 4156 |
| Rim Rec | 10.00W |

Load capacity (Kg)

| | |
|------------|------|
| km/h / bar | 9.00 |
| 70 | 6000 |

Printed on 24/04/2024 10:17

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..