

## AS 504 - Technical Specifications



### Description

AS 504 is an agro-industrial tire mainly designed for soil tillage, implement and material-handling operations. This tire, which features excellent self-cleaning properties and increased grip, is suitable for field trailers and telehandlers. AS 504 is available in several versions to meet specific end-user requirements: an "HD" version with a special cut-and-chip resistance compound, while the "special" version has a reinforced casing that ensures a longer tire life.

### UM

International Standard

### Construction

 BIAS

### Machinery

Agriculture: Telehandler • Field Trailer  
Industrial: Telehandler

Version	INDUSTRIAL
Type	TL
Tyre Size	400/80 - 24
LI/SS	156 A8

## Dimensions International Standard

Section Width (mm)	394
Overall Diameter (mm)	1262
Static Loaded Radius (mm)	566
Rolling Circumference (mm)	3655
SRI (mm)	600
Rim Rec	W 13
Rim Alt	W 12 ; W 14 L

## Load capacity (Kg)

km/h / bar	3.80
10	5000
25	4240
30	4160
40	4000

Printed on 25/04/2024 20:49

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..