

AT 316 - Technical Specifications



Description

AT 316 is suitable for compact utility tractors in municipality and maintenance applications. The special tread design provides excellent traction without compromising field protection - an essential feature for this kind of application. AT 316 is also available as "aramid-belted" version to provide increased puncture resistance.

UM

International Standard

Construction

 BIAS

Machinery

Agriculture: Compact Utility Tractor

Version	STANDARD
Type	TL
Tyre Size	24 X 12.00 - 12

Dimensions International Standard

Ply Rating	4
Section Width (mm)	315
Overall Diameter (mm)	610
Static Loaded Radius (mm)	271
Rolling Circumference (mm)	1769
Rim Rec	10.50 I - 55 ; I - 70 ; I - 90
ECE	E11-106R-004082

Load capacity (Kg)

km/h / bar	1.40
15	775

Printed on 23/04/2024 13:44

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..