



## AT 621 - Data Sheet



### Description

AT 621 is suitable for backhoe loaders and compact loaders in all digging and loading operations in agriculture. The AT 621 tire features an extra deep tread which ensures great cut and chip resistance and higher durability. In addition, this BKT tire ensures great durability and self cleaning properties. AT 621 is available in several versions to meet the most differing user requirements.

### UM

US Standard

### Construction

 BIAS

### Machinery

Agriculture: Compact Loader • Backhoe Loader

Industrial: Backhoe Loader • Loader

SIZE	Version	USACode	TRA Code	LI/SS	LI/SS DRIVE WHEEL	LI/SS FREE ROLLING	PR	RIM REC	RIM ALT	SW	OD	SLR	RC	Type	ECE
33 X 12.5 - 15	STANDARD	94037209	R4				8	10.00 F SDC		12.5	33.5	15.5	98.7	TT	E11-106R-005230
10.0/75 - 15.3	STANDARD	94070619		127 A6			10	9.0		10.5	30.7	14.7	93.9	TL	E11-106R-007466
12.5/70 - 16	STANDARD	94054169	R4				14	10 LB		12.4	33.7	15.2	101.7	TL	
12.5/70 - 16	STANDARD	94054350	R4				14	10 LB		12.4	33.7	15.2	101.7	TT	
12.5/70 - 16	STANDARD	94028511	R4				8	10 LB		12.4	33.7	15.2	101.7	TL	E11-106R-005295
9.00 - 16	INDUSTRIAL	94051595		137 A6			16	6.50 H	6.00 G	10.2	36.4	0	0	TT	E11-106R-005364
12.5/80 - 18	INDUSTRIAL HD	94032730	R4		135 A8	148 A8	16	W 9	11.0	12.1	38.9	17.1	114.8	TL	E11-106R-005365
12.5/80 - 18	SPECIAL	94035960	R4		129 A8	142 A8	12	W 9	11.0	12.1	38.9	17.1	114.8	TL	E11-106R-005329
12.5/80 - 18	STANDARD	94019731	R4		129 A8	142 A8	12	W 9	11.0	12.1	38.9	17.1	114.8	TL	E11-106R-003388
12.5/80 - 18	STANDARD	94019748	R4		135 A8	148 A8	16	W 9	11.0	12.1	38.9	17.1	114.8	TT	E11-106R-006957
12.5/80 - 18	STANDARD	94026258	R4		135 A8	148 A8	16	W 9	11.0	12.1	38.9	17.1	114.8	TL	E11-106R-006957
12.5/80 - 18	STANDARD	94019724	R4		129 A8	142 A8	12	W 9	11.0	12.1	38.9	17.1	114.8	TT	E11-106R-003388
15.5/60 - 18	STANDARD	94028542	R4	139 A2			10	W 13		15.5	37	16.9	113	TL	E11-106R-003575
15.5/60 - 18	STANDARD	94048229	R4	141 A2			12	W 13		15.5	37	16.9	113	TL	E11-106R-004651
15.5/70 - 18 (400/70 - 18)	STANDARD	94041602	R4				10	W 13		15.7	40.6	18.7	122.5	TL	E11-106R-005260
385/65 D 19.5	STANDARD	94065912		165 A2			16	11.75	12.25	15.4	40.2	18.8	123.5	TL	E11-106R-006419
12.5 - 20	STANDARD	94058488	R4				12	11.0		12.8	40.9	0	0	TT	E11-106R-005293
17.5/65 - 20	STANDARD	94028559	R4				10	W 14 L		17.7	42.9	19.3	129.7	TL	E11-106R-005262
400/70 - 20	STANDARD	94060658	R4	152 B/168 A2			16	13	12 SDC ; 13 SDC ; 14	15.9	42.9	19.4	128.8	TL	
400/70 - 20	STANDARD	94051526	R4	149 A8				13	12 SDC ; 13 SDC ; 14	15.9	42.9	19.4	128.8	TL	E11-106R-005289
42 X 17 - 20	STANDARD	94037216	R4				10	14.00 TG SDC		17	42.2	18.9	125.9	TT	E11-106R-005294
16.9 - 24	INDUSTRIAL	94035397	R4	149 A8			12	DW 15 L	DW 14 L	17.7	51.3	23.2	153.8	TL	E11-106R-005374
17.5L -	STANDARD	94027491	R4	139 A8			8	DW 15	DW 14 L	17.7	49.4	22	147.7	TL	E11-

<b>24</b>							L									106R-005267
<b>19.5L - 24</b>	STANDARD	94046232	R4	151 A8		12	DW 16 L		19	51.4	23.1	155	TL			E11-106R-005373
<b>18.4 - 26</b>	STANDARD	94031801	R4	156 A8		12	DW 16 L	DW 15 L	18.9	56.1	25.6	168.8	TL			E11-106R-003634
<b>16.9 - 28</b>	INDUSTRIAL	94069675	R4	154 A8		14	DW 15 L	DW 14 L	17.7	55.5	25.2	165.3	TL			E11-106R-007209
<b>16.9 - 28</b>	INDUSTRIAL	94016792	R4	152 A8		12	DW 15 L	DW 14 L	17.7	55.5	25.2	165.3	TT			E11-106R-003635
<b>16.9 - 28</b>	INDUSTRIAL	94016808	R4	152 A8		12	DW 15 L	DW 14 L	17.7	55.5	25.2	165.3	TL			E11-106R-003635
<b>16.9 - 30</b>	INDUSTRIAL	94027507	R4	153 A8		12	DW 15 L	DW 14 L	17.7	57.5	26.4	173.1	TL			E11-106R-005375

Printed on 24/04/2024 05:57

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..