

## AT 625 - Technical Specifications



### Description

AT 625 is suitable for backhoe loaders and compact loaders in all farming digging and loading operations. Its extra deep tread ensures increased puncture resistance and durability. AT 625 features excellent traction and stability as well as improved cut and chip resistance.

### UM

International Standard

### Construction

 BIAS

### Machinery

Industrial: Backhoe Loader • Compact Loader

|           |            |
|-----------|------------|
| Version   | INDUSTRIAL |
| Type      | TT         |
| Tyre Size | 16.9 - 28  |
| LI/SS     | 152 A8     |

## Dimensions International Standard

|                            |         |
|----------------------------|---------|
| Ply Rating                 | 12      |
| Section Width (mm)         | 450     |
| Overall Diameter (mm)      | 1415    |
| Static Loaded Radius (mm)  | 645     |
| Rolling Circumference (mm) | 4254    |
| Rim Rec                    | DW 15 L |
| Rim Alt                    | DW 14 L |
| TRA Code                   | R4      |

## Load capacity (Kg)

|            |      |
|------------|------|
| km/h / bar | 2.60 |
| 40         | 3550 |

Printed on 24/04/2024 21:12

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..