

AW 09 - Technical Specifications



Description

AW 09 has been developed for soil tillage, hay harvesting and transport applications with implements, balers and trailers. It is ideal for modern farming both on and off the road. Its reinforced carcass ensures high load capacity and a longer service tire life. AW 09 has been designed with a special cut-and-chip-resistant compound that provides extraordinary stubble resistance.

UM

International Standard

Construction

 BIAS

Machinery

Agriculture: Baler • Hay Harvester • Implement Machinery
• Trailer

Version	STANDARD
Type	TL
Tyre Size	260/70 - 15.3
LI/SS DRIVE WHEEL	119 A8
LI/SS FREE ROLLING	131 A8

Dimensions International Standard

Section Width (mm)	268
Overall Diameter (mm)	753
Static Loaded Radius (mm)	335
Rolling Circumference (mm)	2206
Rim Rec	9.00
ECE	E4-106R-000374

Load capacity (Kg)

	km/h / bar	5.00
	10 FR	2730
	25 FR	2320
	30 FR	2185
	40 FR	1950
	10 DW	1905
	25 DW	1620
	30 DW	1525
	40 DW	1360

Printed on 23/04/2024 17:04

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..