



AW-18 - Data Sheet



Description

AW-18 has been designed for trailers and implement machinery employed in soil tillage operations. Its special design with non-directional lugs and a rounded shoulder area avoids crop damages while maneuvering. The tread pattern has been specifically developed to ensure top self-cleaning properties. AW-18 also stands for best driving comfort and reduced fuel consumption.

UM

US Standard

Construction

 BIAS

Machinery

Agriculture: Implement Machinery

| SIZE | Version | USACode | LI/SS FREE ROLLING | RIM REC | RIM ALT | SW | OD | Type | ECE |
|-----------------------------------|----------|----------|--------------------|---------|---------|------|------|------|-----------------|
| 11.5/80 - 15.3 (300/80 - 15.3) | STANDARD | 94064045 | 139 A8 | 9.00 | | 11.7 | 33.3 | TL | E11-106R-006020 |

Printed on 27/04/2024 10:20

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..