

AW 702 IND - Technical Specifications



Description

AW 702 IND has been developed for Industrial trailers applications. This heavy-duty tire has been designed by BKT to provide a new level of durability.

UM

International Standard

Construction

 BIAS

Machinery

Industrial: Trailer

| | |
|--------------------|------------|
| Version | INDUSTRIAL |
| Type | TT |
| Tyre Size | 6.00 - 16 |
| LI/SS FREE ROLLING | 103 A8 |

Dimensions International Standard

| | |
|----------------------------|-----------------|
| Ply Rating | 8 |
| Section Width (mm) | 169 |
| Overall Diameter (mm) | 722 |
| Static Loaded Radius (mm) | 337 |
| Rolling Circumference (mm) | 2150 |
| Rim Rec | 4.00 E |
| Rim Alt | 4.50 E ; 4½ K |
| ECE | E11-106R-004358 |

Load capacity (Kg)

| | km/h / bar | 4.00 |
|--|------------|------|
| | 10 FR | 1225 |
| | 25 FR | 1040 |
| | 30 FR | 980 |
| | 40 FR | 875 |

Printed on 25/04/2024 16:53

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..