

AW 705 - Technical Specifications



Description

AW 705 has been developed for implement machinery, trailers and balers in soil tillage and haulage applications. It is ideal for modern farming thanks to improved durability and high load capacity.

UM

International Standard

Construction

 BIAS

Machinery

Agriculture: Baler • Implement Machinery • Trailer

Version	STANDARD
Type	TL
Tyre Size	15.0/70 - 18
LI/SS FREE ROLLING	151 A8

Dimensions International Standard

Ply Rating	16
Section Width (mm)	405
Overall Diameter (mm)	1010
Static Loaded Radius (mm)	447
Rolling Circumference (mm)	3092
Rim Rec	13.00
Rim Alt	13 ; W 13
ECE	E4-106R-002266

Load capacity (Kg)

	km/h / bar	4.25
	10 FR	4830
	25 FR	4105
	30 FR	3865
	40 FR	3450

Printed on 20/04/2024 04:49

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..