

AW 711 - Technical Specifications

Description

AW 711 is a radial implement tire specially designed for modern farming, and suitable for haulage, hay harvesting and soil tillage applications. Thanks to its special tread compound, AW 711 has an extended product life-cycle, whether it is used on soft or hard surfaces. The low rolling resistance during on-road travel ensures significant savings in fuel consumption. Thanks to the VF technology, AW 711 can carry heavy loads at low inflating pressure.



UM

US Standard

Construction

 RADIAL

Machinery

Agriculture: Hay Harvester • Implement Machinery

Version	STUBBLE RESISTANT
Type	TL
Tyre Size	265/70 R 16.5 (10 R 16.5)
LI/SS	134 A8/B

Dimensions US Standard

Usa code	94053292
Section Width (inch)	10.4
Overall Diameter (inch)	30.4
Static Loaded Radius (inch)	13.5
Rolling Circumference (inch)	90
Rim Rec	8.25
ECE	E11-106R-002978

Load capacity (lbs)

mph / psi	12	17	23	29	35	41	46	52	58
30	1500	1970	2390	2770	3190	3600	3880	4250	4670
25	1500	1970	2390	2770	3190	3600	3880	4250	4670
20	1680	2200	2680	3100	3560	4030	4350	4770	5240
15	1790	2350	2840	3280	3790	4290	4630	5070	5570
10	1900	2480	3010	3480	4010	4540	4910	5370	5900
5	2110	2760	3340	3870	4450	5050	5450	5960	6550

Printed on 10/12/2023 11:32

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..