

## AW 726 - Technical Specifications



### Description

AW 726 has been specially designed for trailers in transport operations. It is best suited for both on-and-off-the-road usage. AW 726 shows excellent road performance and self-cleaning features. The block pattern design provides an extended tire life-cycle.

### UM

International Standard

### Construction

 BIAS

### Machinery

Agriculture: Trailer

Version	ARAMID BELTED
Type	TL
Tyre Size	11.5/80 - 15.3
LI/SS DRIVE WHEEL	126 A8
LI/SS FREE ROLLING	139 A8

## Dimensions International Standard

Ply Rating	14
Section Width (mm)	300
Overall Diameter (mm)	855
Static Loaded Radius (mm)	363
Rolling Circumference (mm)	2531
Rim Rec	9.00

## Load capacity (Kg)

km/h / bar	4.80
10 FR	3400
25 FR	2890
30 FR	2720
40 FR	2430
10 DW	2380
25 DW	2025
30 DW	1905
40 DW	1700

Printed on 27/04/2024 04:43

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..