

## AW 729 - Technical Specifications



### Description

AW 729 is an agricultural tire specifically designed for transport, hay harvesting, baling and soil tillage applications. Its rounded shoulder and three central grooves tread design provide low soil compaction and avoids damages to the field.

AW 729 is the ideal tire for modern farming, and it is suited for both on-and-off-the-road usage.

### UM

US Standard

### Construction

 BIAS

### Machinery

Agriculture: Baler • Implement Machinery • Trailer

Version	STANDARD
Type	TL
Tyre Size	480/45 - 17
LI/SS DRIVE WHEEL	134 A8
LI/SS FREE ROLLING	146 A8

## Dimensions US Standard

Usa code	94068975
Section Width (inch)	18.9
Overall Diameter (inch)	34.1
Static Loaded Radius (inch)	15.7
Rolling Circumference (inch)	99.4
Rim Rec	16.00
ECE	E11-106R-006798

## Load capacity (lbs)

mph / psi	46
5 FR	9240
15 FR	7855
20 FR	7390
25 FR	6600
5 DW	6550
15 DW	5570
20 DW	5240
25 DW	4680

Printed on 25/04/2024 20:11

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..