

AW 909 - Technical Specifications



Description

AW 909 has been developed for soil tillage, hay harvesting and transport applications with implement machinery, trailers and balers. It is ideal for modern farming both on and off the road.

UM

International Standard

Construction

 BIAS

Machinery

Agriculture: Baler • Implement Machinery • Trailer

Version	STANDARD
Type	TL
Tyre Size	11.5/80 - 15.3
LI/SS FREE ROLLING	141 A8

Dimensions International Standard

Ply Rating	16
Section Width (mm)	300
Overall Diameter (mm)	844
Static Loaded Radius (mm)	370
Rolling Circumference (mm)	2473
Rim Rec	9.00
ECE	E4-106R-002752

Load capacity (Kg)

	km/h / bar	5.40
	10 FR	3605
	25 FR	3065
	30 FR	2885
	40 FR	2575

Printed on 23/04/2024 17:22

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..