

## BK 308 - Technical Specifications



### Description

BK 308 has been specially designed for trailers and utility tractors. It features excellent traction on all surfaces and tread tie bars to reduce tread groove cracking. The strong casing provides excellent durability and puncture resistance whereas the special tread compound ensures a longer service life.

### UM

International Standard

### Construction

 BIAS

### Machinery

Agriculture: Compact Utility Tractor • Trailer

Version	STANDARD
Type	TT
Tyre Size	6.50 - 20
LI/SS	112 A6

# Dimensions International Standard

Ply Rating	10
Section Width (mm)	190
Overall Diameter (mm)	865
Rim Rec	5.50 F
Rim Alt	4.00 E ; 5.00 F
ECE	E11-106R-003563

## Load capacity (Kg)

km/h / bar	4.8
30	1120

Printed on 03/05/2024 15:48

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..