

BK 4040 - Technical Specifications



Description

BK 4040 has been specifically designed for agricultural trailers in haulage application. The strong casing ensures best load capacity and durability.

UM

US Standard

Construction

 BIAS

Machinery

Agriculture: Trailer

Version	STANDARD
Type	TT
Tyre Size	7.00 - 16

Dimensions US Standard

Usa code	94044481
Ply Rating	12
Section Width (inch)	7.8
Overall Diameter (inch)	30.3
Rim Rec	5.50
Rim Alt	5.00 F
ECE	E11-106R-005300

Load capacity (lbs)

mph / psi	68
20	2910

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.

Printed on 07/12/2024 15:47

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..