# COMMANDER 3 RIB - Technical Specifications

## Description

COMMANDER 3 RIB is a 3-rib pattern front tire designed for soil tillage and haulage operations. It provides excellent durability and load capacity thanks to the optimized weight distribution on center and shoulder ribs. The strong casing along with the cut-and-chip resistant compound ensure outstanding puncture resistance.

## UM

US Standard

## Construction

BIAS

## Machinery

Agriculture: 2WD Tractor

| | |
|---|---|
| **Version** | STANDARD |
| **Type** | TT |
| **Tyre Size** | 6.00 - 16 |
| **LI/SS** | 91 A8 |

## Dimensions US Standard

| | |
|---|---|
| **Usa code** | 94046911 |
| **Ply Rating** | 8 |
| **Section Width (inch)** | 6.9 |
| **Overall Diameter (inch)** | 29.1 |
| **Rim Rec** | 4.50 E |
| **Rim Alt** | 4.00 E ; 5.00 F |
| **ECE** | E11-106R-004415 |
| **TRA Code** | F2 |

## Load capacity (lbs)

| mph / psi | 68 |
|---|---|
| **25** | 1360 |

Printed on 29/04/2024 08:51

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..