

COMMANDER TWIN RIB - Technical Specifications



Description

COMMANDER TWIN RIB is a 4-rib pattern tire with shoulder notches providing excellent grip. Its wider tread profile ensures good weight distribution. The strong casing along with a superior tread compound provide a longer tire life. COMMANDER TWIN RIB is perfect for soil tillage and haulage applications.

UM

US Standard

Construction



Machinery

Agriculture: 2WD Tractor

| Version | STANDARD |
|-----------|-----------|
| Туре | π |
| Tyre Size | 5.00 - 15 |
| LI/SS | 76 A8 |

Dimensions US Standard

| Usa code | 94059669 |
|-------------------------|----------|
| Ply Rating | 6 |
| ТМРН | 1 |
| Section Width (inch) | 5.7 |
| Overall Diameter (inch) | 26.2 |
| Rim Rec | 4.00 E |
| TRA Code | F2 |

Load capacity (lbs)

| mph / psi | 60 |
|-----------|-----|
| 25 | 880 |

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.

Printed on 02/05/2025 21:45

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..