

# COMMANDER TWIN RIB - Technical Specifications



## Description

COMMANDER TWIN RIB is a 4-rib pattern tire with shoulder notches providing excellent grip. Its wider tread profile ensures good weight distribution. The strong casing along with a superior tread compound provide a longer tire life. COMMANDER TWIN RIB is perfect for soil tillage and haulage applications.

## UM

International Standard

## Construction

 BIAS

## Machinery

Agriculture: 2WD Tractor

Version	STANDARD
Type	TT
Tyre Size	6.50 - 16
LI/SS	98 A6

## Dimensions International Standard

Ply Rating	8
Section Width (mm)	180
Overall Diameter (mm)	761
Rim Rec	4.50 E
Rim Alt	4.00 E ; 5.00 F ; 5.50 F
ECE	E11-106R-004107
TRA Code	F2

## Load capacity (Kg)

km/h / bar	4.20
30	750

Printed on 20/04/2024 13:04

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..