

CON STAR - Technical Specifications



Description

CON STAR is particularly suitable for compact loaders and telehandlers in agro-industrial, lifting and loading applications. It features great traction along with excellent vertical and horizontal stability. CON STAR has been made of a cut-and-chip-resistant compound contributing to an extended tire life-cycle.

UM

International Standard

Construction

 BIAS

Machinery

Agriculture: Compact Loader • Telehandler
Industrial: Compact Loader • Telehandler

Version	INDUSTRIAL
Type	TL
Tyre Size	440/80 - 24 (17.0/80 - 24)
LI/SS	168 A8

Dimensions International Standard

Ply Rating	22
Section Width (mm)	455
Overall Diameter (mm)	1315
Static Loaded Radius (mm)	610
Rolling Circumference (mm)	3986
SRI (mm)	625
Rim Rec	DW 14 L
Rim Alt	DW 13 ; DW 13 L ; DW 15 L
ECE	E11-106R-003027

Load capacity (Kg)

km/h / bar	5.00
40	5600

Printed on 17/04/2024 21:52

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..