

CONTAINER KING - Data Sheet



Description

CONTAINER KING has been designed for reach stackers in intermodal transport and logistics applications. This extraordinary tire is made of a highly wear-and-tear-resistant tread compound which minimizes tread cracks. CONTAINER KING ensures an extended tire life-cycle plus exceptional stability in lift mode.

UM

US Standard

Construction

 BIAS

Machinery

Industrial: Reach Stacker

SIZE	Version	USACode	TRA Code	PR	RIM REC	RIM ALT	OW	OD	SLR	RC	Type
12.00 - 24	INDUSTRIAL	94069798	IND4	24	8.5	8.0	13	50.6	0	0	TT
18.00 - 25	INDUSTRIAL	94036516	IND4	40	13.00/2.5	15.00/2.5	20.8	65.9	30.1	195.1	TL
18.00 - 33	INDUSTRIAL	94064526	IND4	40	13.00/2.5		20.1	74.6	33.5	229.1	TL

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.

Printed on 23/05/2025 05:12

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..