

DON 2000 - Technical Specifications



Description

DON 2000 is a suitable for transport operations with trailers and light trucks both on and off the road. It ensures extra durability along with high performance during the entire product life-cycle.

UM

International Standard

Construction



Machinery

Agriculture: Light Truck • Trailer

| Version | STANDARD |
|-----------|-----------|
| Туре | TT |
| Tyre Size | 7.50 - 16 |

Dimensions International Standard

| Ply Rating | 16 |
|-----------------------|--------|
| Section Width (mm) | 216 |
| Overall Diameter (mm) | 840 |
| Rim Rec | 6.00 G |
| Rim Alt | 5.50 F |

Load capacity (Kg)

| km/h / bar | 7.60 |
|------------|------|
| 100 LS | 1600 |
| 100 LD | 1400 |

Printed on 03/05/2024 02:58

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..