

## EARTHMAX SR 30 - Data Sheet



### Description

EARTHMAX SR 30 (E-3/L-3) is an **All Steel** radial tire which is dual-purposed for loaders and articulated dump trucks. The multi-layer steel belts and the rigid block pattern provide excellent traction, stability and durability. The special cut-resistant compound makes EARTHMAX SR 30 the ideal solution for a variety of harsh operating conditions.

### UM

International Standard

### Construction

 RADIAL

### Machinery

OTR: Articulated Dump Truck (ADT) • Dozer • Loader

SIZE	Version	TRA Code	Star R	LI/SS	RIM REC	RIM ALT	OW	OD	SLR	RC	Type	TKPH
15.5 R 25	CUT RESISTANT COMPOUND	E3/L3	**/*	160 B/169 A2	12.00/1.3	-	397	1276	574	3809	TL	130
17.5 R 25	CUT RESISTANT COMPOUND	E3/L3	**/*	167 B/176 A2	14.00/1.5		446	1347	606	4021	TL	150
17.5 R 25	CUT RESISTANT COMPOUND	L3	***	188 A2	14.00/1.5		446	1347	606	4021	TL	
20.5 R 25	CUT RESISTANT COMPOUND	L3	**	193 A2	17.00/2.0	17.00/1.7	529	1487	663	4439	TL	
20.5 R 25	CUT RESISTANT COMPOUND	E3/L3	**/*	177 B/186 A2	17.00/2.0	17.00/1.7	529	1487	663	4439	TL	170
23.5 R 25	CUT RESISTANT COMPOUND	E3/L3	**/*	185 B/195 A2	19.50/2.5		612	1607	711	4797	TL	200
26.5 R 25	CUT RESISTANT COMPOUND	E3/L3	**/*	193 B/202 A2	22.00/3.0		689	1742	766	5200	TL	230
26.5 R 25	CUT RESISTANT COMPOUND	E3	**	193 B	22.00/3.0		689	1742	766	5200	TL	230
26.5 R 25	CUT RESISTANT COMPOUND	L3	*	202 A2	22.00/3.0		689	1742	766	5200	TL	
29.5 R 25	CUT RESISTANT COMPOUND	E3/L3	**/*	200 B/208 A2	25.00/3.5		765	1861	818	5555	TL	270
29.5 R 25	CUT RESISTANT COMPOUND	L3	*	208 A2	25.00/3.5		765	1861	818	5555	TL	
29.5 R 25	CUT RESISTANT COMPOUND	E3	**	200 B	25.00/3.5		765	1861	818	5555	TL	270

Printed on 27/04/2024 00:52

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..