

EARTHMAX SR 31 - Technical Specifications



Description

EARTHMAX SR 31 is an All Steel radial tire specially designed for articulated dump trucks and wheel loaders. Its multiply steel belts provide extraordinary strength and stability, whilst the non-directional rigid block pattern stands for both excellent traction and maneuverability even on muddy ground. In addition to outstanding riding comfort, EARTHMAX SR 31 features a special tread compound which is particularly cut-and-heat resistant. The radial casing structure also provides reduced rolling resistance offering significant fuel savings.

UM

International Standard

Construction

 RADIAL

Machinery

Industrial: Dozer • Loader

OTR: Articulated Dump Truck (ADT) • Dozer • Loader

Version	CUT RESISTANT COMPOUND
Type	TL
Tyre Size	26.5 R 25
LI/SS	193 B/202 A2

Dimensions International Standard

TKPH	230
Overall Width (mm)	689
Overall Diameter (mm)	1742
Static Loaded Radius (mm)	766
Rolling Circumference (mm)	5200
Rim Rec	22.00/3.0
Star Rating	**/*
TRA Code	E3/L3

Load capacity (Kg)

km/h / bar	4.00	4.25	4.50	4.75	5.00	5.25
50	9500	9750	10300	10600	11200	11500
10	12850	13200	14000	14500	15000	--

Printed on 27/04/2024 12:01

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..