



## EARTHMAX SR 32 - Data Sheet



### Description

EARTHMAX SR 32 is a non-directional wide-base radial tire particularly suitable for scrapers. The tire features a strong All Steel casing and a special tread compound providing excellent cut and puncture resistance as well as durability. Additional traits are exceptional traction and flotation even during heavy-duty operations.

### UM

International Standard

### Construction

 RADIAL

### Machinery

OTR: Scraper

SIZE	Version	TRA Code	Star R	LI/SS	RIM REC	RIM ALT	OW	OD	SLR	RC	Type	TKPH
29.5 R 29	CUT RESISTANT COMPOUND	E3	**	202 B	25.00/3.5	24.00/3.5	765	1980	883	6009	TL	288
33.25 R 29	CUT RESISTANT COMPOUND	E3	**	209 B	27.00/3.5	26.00/3.5	845	2080	915	6250	TL	346
37.25 R 35	CUT RESISTANT COMPOUND	E3	**	218 B	31.00/4.0		963	2381	1062	7229	TL	453
40.5/75 R 39	CUT RESISTANT COMPOUND	E3	**	225 B	32.00/4.5		985	2610	1164	7924	TL	505
40.5/75 R 39	STANDARD COMPOUND	E3	**	225 B	32.00/4.5		985	2610	1164	7924	TL	689

Printed on 27/04/2024 07:14

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..