

# EARTHMAX SR 33 - Technical Specifications



## Description

Earthmax SR 33 is a radial tire for multipurpose trucks. Its multi-block tread pattern has been specially designed to guarantee extraordinary traction on soft, sandy, or muddy surfaces. Earthmax SR 33 provides outstanding stability in addition to best self-cleaning properties. The strong All Steel casing features excellent durability and resistance to snag and punctures.

## UM

US Standard

## Construction

 RADIAL

## Machinery

Industrial: Universal Vehicle

|           |            |
|-----------|------------|
| Version   | STANDARD   |
| Type      | TL         |
| Tyre Size | 14.00 R 20 |
| LI/SS     | 164/160 J  |

## Dimensions US Standard

|                              |                 |
|------------------------------|-----------------|
| Usa code                     | 94057757        |
| Overall Width (inch)         | 15.4            |
| Overall Diameter (inch)      | 49.2            |
| Static Loaded Radius (inch)  | 22.7            |
| Rolling Circumference (inch) | 151.2           |
| Rim Rec                      | 10.0            |
| Rim Alt                      | 9.0, 10.00W     |
| ECE                          | E11-54R-0016678 |

## Load capacity (lbs)

| mph / psi | 110   |
|-----------|-------|
| 62 LS     | 11000 |
| 62 LD     | 9900  |

Printed on 27/04/2024 07:40

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..