

EARTHMAX SR 35 - Technical Specifications



Description

Earthmax SR 35 is a low-profile All Steel radial tire specially designed for articulated dump trucks and wheel loaders. It is ideal for operations requiring exceptional traction and flotation. Earthmax SR 35 provides both excellent traction and stability. Thanks to its strong steel-belted casing, it ensures extraordinary durability and resistance to snags and punctures. The tire is available as cut-resistant compound for a maximum service life even under severe conditions.

UM

International Standard

Construction

 RADIAL

Machinery

OTR: Articulated Dump Truck (ADT) • Dozer • Loader

| | |
|-----------|-----------------------------|
| Version | CUT RESISTANT COMPOUND |
| Type | TL |
| Tyre Size | 650/65 R 25 (25/65 R 25) |
| LI/SS | 180 B |

Dimensions International Standard

| | |
|----------------------------|-----------|
| TKPH | 202 |
| Overall Width (mm) | 635 |
| Overall Diameter (mm) | 1498 |
| Static Loaded Radius (mm) | 669 |
| Rolling Circumference (mm) | 4493 |
| Rim Rec | 19.50/2.5 |
| Star Rating | ** |
| TRA Code | E3 |
| Tread Depth | 39 |

Load capacity (Kg)

| | | | | |
|------------|------|------|------|------|
| km/h / bar | 4.00 | 4.25 | 4.50 | 4.75 |
| 50 | 7200 | 7350 | 7800 | 8000 |

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.

Printed on 01/05/2025 06:56

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..