

# EARTHMAX SR 412 - Technical Specifications



## Description

EARTHMAX SR 412 (E-4/L-4) is an All Steel radial tire specially designed for Articulated Dump Trucks, Loaders and Dozers. The unique E-4 deep tread pattern ensures excellent traction and exceptional heat resistance. Thanks to its strong All Steel casing and belts, EARTHMAX SR 412 can carry heavy loads providing excellent stability as well as best resistance to snags and punctures. EARTHMAX SR 412 features a squared shoulder design that maximizes ground contact for excellent maneuverability.

## UM

US Standard

## Construction

 RADIAL

## Machinery

OTR: Articulated Dump Truck (ADT) • Dozer • Loader

|           |                             |
|-----------|-----------------------------|
| Version   | CUT RESISTANT COMPOUND      |
| Type      | TL                          |
| Tyre Size | 750/65 R 25<br>(30/65 R 25) |
| LI/SS     | 190 B/202 A2                |

## Dimensions US Standard

|                              |                      |
|------------------------------|----------------------|
| Usa code                     | 94065233             |
| TMPH                         | 157                  |
| Overall Width (inch)         | 30.7                 |
| Overall Diameter (inch)      | 63.1                 |
| Static Loaded Radius (inch)  | 28.1                 |
| Rolling Circumference (inch) | 190.5                |
| Rim Rec                      | 24.00/3.0            |
| Rim Alt                      | 22.00/3.0, 25.00/3.0 |
| Star Rating                  | **/*                 |
| TRA Code                     | E4/L4                |

## Load capacity (lbs)

| mph / psi | 58    | 62    | 65    | 69    |
|-----------|-------|-------|-------|-------|
| 30        | 20900 | 21500 | 22700 | 23400 |
| 5         | 29100 | 30900 | 32000 | 33100 |

Printed on 30/01/2023 17:30

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..