

EARTHMAX SR 43 - Data Sheet



Description

EARTHMAX SR 43 (L-4) is an All Steel radial tire specially designed for wheel loaders operating in severe rocky conditions, primarily underground mining. The tire delivers excellent performance in load and carry operations in open pit mines, quarries and scrap yards. Its unique tread design offers superior traction and stability. Thanks to its All Steel casing, EARTHMAX SR 43 (L-4) provides excellent durability, resistance to snags and punctures as well as a long service life.

UM

US Standard

Construction

 RADIAL

Machinery

OTR: Loader

SIZE	Version	USACode	TRA Code	Star R	LI/SS	RIM REC	RIM ALT	OW	OD	SLR	RC	Type	Tread Depth
29.5 R 25	CUT RESISTANT COMPOUND	94063291	L4	**	216 A2	25.00/3.5		30.9	73.8	33.3	222.2	TL	77
29.5 R 25	CUT RESISTANT COMPOUND	94063390	L4	***	221 A2	25.00/3.5		30.9	73.8	33.3	222.2	TL	77
29.5 R 29	CUT RESISTANT COMPOUND	94051021	L4	***	223 A2	25.00/3.5	24.00/3.5, 26.00/3.5	30.2	78.9	35.6	237.4	TL	78
875/65 R 29 (35/65 R 29)	CUT RESISTANT COMPOUND	94071098	L4	***	228 A2	27.00/3.5	27.00/3.0; 28.00/3.5	33.5	73.9	33.2	224.5	TL	77
35/65 R 33	CUT RESISTANT COMPOUND	94068869	L4	***	229 A2	28.00/3.5		35.4	81.7	37.7	252.4	TL	77
35/65 R 33	CUT RESISTANT COMPOUND	94067312	L4	**	224 A2	28.00/3.5		35.4	81.7	37.7	252.4	TL	77
35/65 R 33	CUT RESISTANT COMPOUND	94069903	E4/L4	****/***		28.00/3.5		35.4	81.7	37.7	252.4	TL	77
35/65 R 33	CUT RESISTANT COMPOUND	94069910	SH4	****		28.00/3.5		35.4	81.7	37.7	252.4	TL	77

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.

Printed on 21/05/2025 22:55

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..