

EARTHMAX SR 452 - Data Sheet



Description

EARTHMAX SR 452 is an All Steel radial tire specifically designed for Rigid Dump Trucks in transport operations. Its unique E-4 deep tread pattern stands for excellent traction and exceptional heat resistance, minimizing vibration and noise to provide best handling and comfort. Its strong steel casing and belts provide excellent stability and resistance to cuts and punctures. EARTHMAX SR 452 features a squared shoulder that maximizes ground contact for excellent maneuverability.

UM

US Standard

Construction

 RADIAL

Machinery

OTR: Rigid Dump Truck

SIZE	Version	USACode	TRA Code	Star R	LI/SS	RIM REC	RIM ALT	OW	OD	SLR	RC	Type	TMPH
24.00 R 35	CUT RESISTANT COMPOUND	94063383	E4	**	209 B	17.00/3.5		26	85.4	39.2	264.9	TL	243
24.00 R 35	CUT RESISTANT COMPOUND	94063970	E4	***	212 B	17.00/3.5		26	85.4	39.2	264.9	TL	243
24.00 R 35	STANDARD COMPOUND	94063833	E4	**	209 B	17.00/3.5		26	85.4	39.2	264.9	TL	284
24.00 R 35	STANDARD COMPOUND	94063987	E4	***	212 B	17.00/3.5		26	85.4	39.2	264.9	TL	284

Printed on 07/05/2024 18:22

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..