

EARTHMAX SR 47 - Data Sheet



Description

EARTHMAX SR 47 (E-4) is an **All Steel** radial tire specially designed for rigid haul trucks operating in conditions requiring maximum rock cut and puncture resistance. The E-4 tread depth and the unique tread design ensure long wear even on long hauls, thus reducing downtime and increasing productivity. Available in standard and cut-resistant compounds.

UM

International Standard

Construction

 RADIAL

Machinery

OTR: Rigid Dump Truck

SIZE	Version	TRA Code	Star R	LI/SS	RIM REC	RIM ALT	OW	OD	SLR	RC	Type	TKPH
18.00 R 33	CUT RESISTANT COMPOUND	E4	***	195 B	13.00/2.5		510	1885	867	5674	TL	168
18.00 R 33	CUT RESISTANT COMPOUND	E4	**	191 B	13.00/2.5	--	510	1885	867	5674	TL	168
18.00 R 33	HEAT RESISTANT	E4	**	191 B	13.00/2.5	--	510	1885	867	5674	TL	228
18.00 R 33	STANDARD COMPOUND	E4	***	195 B	13.00/2.5		510	1885	867	5674	TL	204
18.00 R 33	STANDARD COMPOUND	E4	**	191 B	13.00/2.5	--	510	1885	867	5674	TL	204
21.00 R 33	CUT RESISTANT COMPOUND	E4	**	200 B	15.00/3.0	--	575	2001	918	6113	TL	227
21.00 R 33	STANDARD COMPOUND	E4	**	200 B	15.00/3.0	--	575	2001	918	6113	TL	270
21.00 R 35	CUT RESISTANT COMPOUND	E4	**	201 B	15.00/3.0	17.00/3.0	585	2045	944	6313	TL	261
21.00 R 35	HEAT RESISTANT COMPOUND	E4	**	201 B	15.00/3.0	17.00/3.0	585	2045	944	6313	TL	355
21.00 R 35	STANDARD COMPOUND	E4	**	201 B	15.00/3.0	17.00/3.0	585	2045	944	6313	TL	305
24.00 R 35	CUT RESISTANT COMPOUND	E4	**	209 B	17.00/3.5	--	670	2181	983	6565	TL	266
24.00 R 35	CUT RESISTANT COMPOUND	E4	***	212 B	17.00/3.5	--	670	2181	983	6565	TL	266
24.00 R 35	STANDARD COMPOUND	E4	**	209 B	17.00/3.5	--	670	2181	983	6565	TL	315
24.00 R 35	STANDARD COMPOUND	E4	***	212 B	17.00/3.5	--	670	2181	983	6565	TL	315

Printed on 14/04/2024 06:43

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..