

EARTHMAX SR 48 - Data Sheet



Description

EARTHMAX SR 48 is an All Steel radial tire specially conceived and engineered for rigid haul trucks. It ensures enhanced traction and extraordinary tread resistance even for the most demanding operations in rocky environments. This tire is ideal for handling heavy loads. The square shoulder design protects the sidewall against cuts and damage. EARTHMAX SR 48 has a strong All Steel casing which provides exceptional protection against shocks and rock perforation resulting in enhanced productivity.

UM

US Standard

Construction



RADIAL

Machinery

OTR: Rigid Dump Truck

SIZE	Version	USACode	TRA Code	Star R	LI/SS	RIM REC	RIM ALT	OW	OD	SLR	RC	Type	Tread Depth	TMPH
24.00 R 35	CUT RESISTANT COMPOUND	94060276	E4	**	209 B	17.00/3.5		26.2	85.8	39.1	260.7	TL	73	212
24.00 R 35	STANDARD COMPOUND	94059713	E4	**	209 B	17.00/3.5		26.2	85.8	39.1	260.7	TL	73	258
27.00 R 49	CUT RESISTANT COMPOUND	94053209	E4	**	223 B	19.50/4.0	--	29.1	105.8	48.2	321.5	TL	86	301
27.00 R 49	HEAT RESISTANT COMPOUND	94054312	E4	**	223 B	19.50/4.0	--	29.1	105.8	48.2	321.5	TL	86	411
27.00 R 49	STANDARD COMPOUND	94055142	E4	**	223 B	19.50/4.0	--	29.1	105.8	48.2	321.5	TL	86	349

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.

Printed on 11/05/2025 20:49

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..