

# **EARTHMAX SR 49 M - Data Sheet**



# **Description**

EARTHMAX SR 49 M is an All Steel radial tire with a special non-directional pattern designed for load haul dumps (LHD), low profile dump trucks (LPDT), loaders and dozers operating in severe rocky conditions primarily in underground mining. EARTHMAX SR 49 M is ideal for severe operations requiring exceptional traction and stability. The L-4 deep tread and the specially formulated UMS (underground mine service) compound provide a longer tread wear in addition to excellent resistance to rock cuts, and punctures.

### **UM**

International Standard

## Construction



# Machinery

OTR: Dozer • Load Haul Dump (LHD) • Loader • Low Profile Dump Truck (LPDT)

| SIZE         | Version                      | TRA<br>Code | Star R | LI/SS           | RIM REC   | RIM ALT                 | ow  | OD   | SLR | RC   | Туре | TKPH |
|--------------|------------------------------|-------------|--------|-----------------|-----------|-------------------------|-----|------|-----|------|------|------|
| 26.5 R<br>25 | CUT RESISTANT COMPOUND       | L4          | **     | 209 A2          | 22.00/3.0 |                         | 708 | 1782 | 801 | 5297 | TL   |      |
| 26.5 R<br>25 | CUT RESISTANT COMPOUND       | E4/L4       | **/*   | 193 B/202<br>A2 | 22.00/3.0 |                         | 708 | 1782 | 801 | 5297 | TL   | 165  |
| 26.5 R<br>25 | CUT RESISTANT COMPOUND       | L4          | *      | 202 A2          | 22.00/3.0 |                         | 708 | 1782 | 801 | 5297 | TL   |      |
| 26.5 R<br>25 | CUT RESISTANT COMPOUND       | E4/L4       | ***/** |                 | 22.00/3.0 |                         | 708 | 1782 | 801 | 5297 | TL   |      |
| 26.5 R<br>25 | CUT RESISTANT COMPOUND (UMS) | E4          | ***    |                 | 22.00/3.0 |                         | 708 | 1782 | 801 | 5297 | TL   |      |
| 29.5 R<br>25 | CUT RESISTANT COMPOUND       | L4          | *      | 208 A2          | 25.00/3.5 |                         | 780 | 1905 | 844 | 5600 | TL   |      |
| 29.5 R<br>25 | CUT RESISTANT COMPOUND       | L4          | **     | 216 A2          | 25.00/3.5 |                         | 780 | 1905 | 844 | 5600 | TL   |      |
| 29.5 R<br>25 | CUT RESISTANT COMPOUND       | E4/L4       | **/*   | 200 B/208<br>A2 | 25.00/3.5 |                         | 780 | 1905 | 844 | 5600 | TL   | 220  |
| 29.5 R<br>25 | CUT RESISTANT COMPOUND       | E4/L4       | ***/** |                 | 25.00/3.5 |                         | 780 | 1905 | 844 | 5600 | TL   |      |
| 29.5 R<br>25 | CUT RESISTANT COMPOUND (UMS) | E4          | ***    |                 | 25.00/3.5 |                         | 780 | 1905 | 844 | 5600 | TL   |      |
| 29.5 R<br>29 | CUT RESISTANT COMPOUND       | L4          | ***    | 223 A2          | 25.00/3.5 | 24.00/3.5,26.00/3.5     | 786 | 2006 | 906 | 6320 | TL   |      |
| 29.5 R<br>29 | CUT RESISTANT COMPOUND (UMS) | E4          | ***    |                 | 25.00/3.5 | 24.00/3.5,<br>26.00/3.5 | 786 | 2006 | 906 | 6320 | TL   |      |

### Printed on 27/04/2024 09:16

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..