

EM 936 SUPER - Technical Specifications



Description

EM 936 SUPER has been specifically designed for excavators and telehandlers in digging and loading operations as well as transport applications. With increased tread width by 8-10%, EM 936 SUPER offers outstanding stability and enhanced riding comfort. It also ensures a high level of handling comfort and provides excellent traction even under heavy-duty service conditions.

UM

US Standard

Construction

 BIAS

Machinery

Industrial: Excavator

Version	STANDARD
Type	TT
Tyre Size	10.00 - 20
LI/SS	146 B

Dimensions US Standard

Usa code	94062690
Ply Rating	16
Section Width (inch)	10.9
Overall Diameter (inch)	42.5
Static Loaded Radius (inch)	19.7
Rolling Circumference (inch)	131.3
Rim Rec	7.5
Rim Alt	7.0 ; 8.0
TRA Code	E2

Load capacity (lbs)

mph / psi	108
30	6600

Printed on 05/05/2024 03:27

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..