

EM 936 - Technical Specifications



Description

EM 936 has been specially designed for excavators and telehandlers in digging and loading operations. Besides, one size is particularly suitable for graders and loaders in grading, loading and transport applications. EM 936 features outstanding riding comfort and enhanced selfcleaning properties. It also ensures a high level of handling comfort and provides excellent traction even under heavyduty service conditions. Its "special" version is made of a special compound.

UM

International Standard

Construction

BIAS

Machinery

Industrial: Excavator • Telehandler

Version	STANDARD
Туре	TL
Tyre Size	20 - 24 (22/70 - 24)
LI/SS	158 B/173 A2

Dimensions International Standard

Ply Rating	12
Overall Width (mm)	535
Overall Diameter (mm)	1390
Static Loaded Radius (mm)	665
Rolling Circumference (mm)	4205
Rim Rec	16.00 T SDC
TRA Code	E2/G2/L2

Load capacity (Kg)

km/h / bar	2.50	3.00
50	4250	-
10	-	6500

Printed on 19/04/2024 20:54

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..