

FARM 2000 - Technical Specifications



Description

The FARM 2000 tire is suitable on tractors for soil tillage applications. It has been designed with a special cut-and-chip resistant compound to ensure better durability. Thanks to its strong casing, FARM 2000 offers high load capacity. It also provides great traction and self-cleaning properties.

UM

US Standard

Construction

✚ BIAS

Machinery

Agriculture: Tractor

Version	STANDARD
Type	TT
Tyre Size	16.9 - 28
LI/SS	139 A8

Dimensions US Standard

Usa code	94002924
Ply Rating	12
Section Width (inch)	16.9
Overall Diameter (inch)	55.9
Static Loaded Radius (inch)	25.9
Rolling Circumference (inch)	171.3
Rim Rec	W 15 L
Rim Alt	W 14 L
ECE	E11-106R-003627
TRA Code	R1

Load capacity (lbs)

mph / psi	36
25	5360

Printed on 06/05/2024 18:06

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..