

FARM 2000 - Technical Specifications



Description

The FARM 2000 tire is suitable on tractors for soil tillage applications. It has been designed with a special cut-and-chip resistant compound to ensure better durability. Thanks to its strong casing, FARM 2000 offers high load capacity. It also provides great traction and self-cleaning properties.

UM

International Standard

Construction

 BIAS

Machinery

Agriculture: Tractor

Version	STANDARD
Type	TT
Tyre Size	250/80 - 18
LI/SS DRIVE WHEEL	115 A8
LI/SS FREE ROLLING	127 A8

Dimensions International Standard

Section Width (mm)	240
Overall Diameter (mm)	870
Static Loaded Radius (mm)	394
Rolling Circumference (mm)	2679
SRI (mm)	410
Rim Rec	W 8
Rim Alt	W7 ; W9
ECE	E11-106R-003519
TRA Code	R1

Load capacity (Kg)

	km/h / bar	2.80
	10 FR	2450
	25 FR	2085
	30 FR	1960
	40 FR	1750
	10 DW	1700
	25 DW	1445
	30 DW	1360
	40 DW	1215

Printed on 26/04/2024 19:42

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..