

FARM HIGHWAY TOUGH - Technical Specifications



Description

FARM HIGHWAY TOUGH is a high-speed tire designed for transport and soil tillage applications with trailers and implement machinery. It provides high load capacity also at high speeds and ensures a long tire life-cycle.

UM

International Standard

Construction

 BIAS

Machinery

Agriculture: Implement Machinery • Trailer

Version	STANDARD
Type	TL
Tyre Size	11L - 15 FI
LI/SS	128 J

Dimensions International Standard

Ply Rating	12
Section Width (mm)	279
Overall Diameter (mm)	777
Static Loaded Radius (mm)	347
Rolling Circumference (mm)	2214
Rim Rec	8 LB
Rim Alt	10 LB ; 8 J
ECE	E11-54R-0017871

Load capacity (Kg)

km/h / bar	6.20
100	1800

Printed on 28/04/2024 09:46

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..