

FL 633 PERFORMA - Technical Specifications



Description

The new All Steel radial tire FL 633 PERFORMA perfectly combines the needs of several agricultural applications with the growing demand for logistics in agriculture. Specifically designed for agro trucks, FL 633 PERFORMA is the innovative solution that enhances both tractor and truck performance features to meet the special needs of modern farming. Thanks to its very strong casing, exceptional load capacity and durability, FL 633 PERFORMA signs the “next level” of flotation tires being suitable for multiple activities in the fields and even for travel on highways reaching up to 100 km/h.

UM

International Standard

Construction

 RADIAL

Machinery

Agriculture: Agro Truck

Version	STANDARD
Type	TL
Tyre Size	600/50 R 22.5
LI/SS	164 J

Dimensions International Standard

Overall Width (mm)	590
Overall Diameter (mm)	1170
Static Loaded Radius (mm)	534
Rolling Circumference (mm)	3559
Rim Rec	AG 20.00
ECE	E11-54R-0017858

Load capacity (Kg)

km/h / bar	6.50
100	5000

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.

Printed on 21/05/2025 17:22

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..