

FL 695 - Technical Specifications



Description

FL 695 has been specifically designed for trailers in construction and transport applications with a unique center block tread pattern. Thanks to its strong casing, FL 695 can carry heavy loads maintaining stability in all conditions and its deep tread ensures optimal self-cleaning during on and off-road applications. Multiple steel cord layers reinforce this pattern against punctures.

UM

International Standard

Construction

 RADIAL

Machinery

Agriculture: Trailer

Industrial: Trailer

Version	STEEL BELTED
Type	TL
Tyre Size	600/55 R 26.5
LI/SS	173 D

Dimensions International Standard

Section Width (mm)	591
Overall Diameter (mm)	1335
Static Loaded Radius (mm)	620
Rolling Circumference (mm)	4090
SRI (mm)	625
Rim Rec	AG20.00
ECE	E11-106R-007937

Load capacity (Kg)

km/h / bar	0.8	1.2	1.6	2.0	2.4	2.8	3.2	3.6	4.0	4.5	5.0	5.5	6.0
65	--	--	--	2925	3380	3835	4225	4615	5070	5395	5720	6110	6500
50	--	--	--	3540	4090	4645	5115	5585	6135	6530	6925	7395	7865
40	--	2920	3625	3980	4600	5220	5750	6280	6900	7340	7780	8310	8840
30	2455	3240	4025	4420	5105	5795	6380	6970	7660	8150	8640	9230	9815
25	2570	3390	4215	4625	5345	6060	6680	7295	8015	8525	9040	9655	10270
20	2685	3540	4400	4830	5580	6330	6975	7615	8370	8905	9440	10085	10725
10	2925	3865	4800	5265	6085	6905	7605	8310	9130	9715	10300	11000	11700

Printed on 05/05/2024 21:45

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..