

FLOTATION 558 - Data Sheet



Description

FLOTATION 558 is a cross-ply flotation tire suitable for hay harvesters/balers, tankers and trailers both on and off the road. It is particularly recommended whenever traction is essential for good soil tillage in addition to high load capacity.

UM

US Standard

Construction

✚ BIAS

Machinery

Agriculture: Baler • Hay Harvester • Tanker • Trailer

SIZE	Version	USACode	LI/SS DRIVE WHEEL	LI/SS FREE ROLLING	PR	RIM REC	RIM ALT	SW	OD	SLR	RC	Type	ECE
400/55 - 22.5	ARAMID BELTED HD	94048298	140 A8/136 B	152 A8/148 B	16	AG 11.75	12.25 ; 13.00 ; AG 13.00	15.9	40.2	17.5	121.4	TL	E11-106R-005350
400/55 - 22.5	STANDARD	94058501	144 A8/140 B	156 A8/152 B	20	AG 11.75	12.25 ; 13.00 ; AG 13.00	15.9	40.2	17.5	121.4	TL	E11-106R-005351
400/55 - 22.5	STANDARD	94006243	138 A8/134 B	150 A8/146 B	14	AG 11.75	12.25 ; 13.00 ; AG 13.00	15.9	40.2	17.5	121.4	TL	E4-106R-002261
400/55 - 22.5	STANDARD	94006250	140 A8/136 B	152 A8/148 B	16	AG 11.75	12.25 ; 13.00 ; AG 13.00	15.9	40.2	17.5	121.4	TL	E4-106R-002262
500/45 - 22.5	ARAMID BELTED HD	94048281	142 A8/138 B	154 A8/150 B	16	AG 16.00		19.7	41.1	18.5	124.7	TL	E11-106R-005352
500/45 - 22.5	STANDARD	94006267	136 A8/132 B	148 A8/144 B	12	AG 16.00		19.7	41.1	18.5	124.7	TL	E4-106R-002307
500/45 - 22.5	STANDARD	94006274	142 A8/138 B	154 A8/150 B	16	AG 16.00		19.7	41.1	18.5	124.7	TL	E4-106R-002315
500/45 - 22.5	STANDARD	94058518	146 A8/142 B	158 A8/154 B	20	AG 16.00		19.7	41.1	18.5	124.7	TL	E11-106R-005353

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.

Printed on 02/05/2025 07:43

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..