

FLOTATION TR 675 - Data Sheet



Description

FLOTATION TR 675 is best suited for field and road transport. It fits trailers and implement machinery. FLOTATION TR 675 has been engineered to provide outstanding traction, high load capacity and a longer tire life.

UM

US Standard

Construction



Machinery

Agriculture: Implement Machinery • Trailer

| SIZE | Version | USACode | LI/SS DRIVE WHEEL | LI/SS FREE ROLLING | PR | RIM REC | RIM ALT | SW | OD | SLR | RC | Туре | ECE |
|------------------|--------------|----------|----------------------|-----------------------|----|-------------|------------------|------|------|------|-------|------|---------------------|
| 500/60 - 22.5 | DUAL BEAD | 94050147 | 155 A8/151 B | 168 A8/164 B | 20 | AG 16.00 | 15.00 ; 17.00 | 20.3 | 46.5 | 21.3 | 141.9 | TL | E11-106R- 004395 |
| 500/60 - 22.5 | STANDARD | 94019786 | 145 A8/142 B | 157 A8/154 B | 12 | AG 16.00 | 15.00 ; 17.00 | 20.3 | 46.5 | 21.3 | 141.9 | TL | E4-106R- 002314 |
| 500/60 - 22.5 | STANDARD | 94019793 | 151 A8/ 148 B | 163 A8/159 B | 16 | AG 16.00 | 15.00 ; 17.00 | 20.3 | 46.5 | 21.3 | 141.9 | TL | E11-106R- 003605 |
| 550/45 - 22.5 | STANDARD | 94047031 | 154 A8/150 B | 166 A8/162 B | 20 | AG 16.00 | | 21.4 | 42.1 | 0 | 0 | TL | E4-106R- 002723 |
| 550/60 - 22.5 | STANDARD | 94019809 | 148 A8/144 B | 160 A8/156 B | 12 | AG 16.00 | | 21.7 | 49.6 | 21.5 | 143.3 | TL | E11-106R- 004396 |
| 550/60 - 22.5 | STANDARD | 94019816 | 154 A8/150 B | 167 A8/163 B | 16 | AG 16.00 | | 21.7 | 49.6 | 21.5 | 143.3 | TL | E11-106R- 004397 |

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.

Printed on 06/05/2025 01:22

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..