

FORESTECH - Technical Specifications



Description

FORESTECH is a BKT bias steel-belted tire, suitable for forestry applications with forwarders. It provides excellent traction even in heavy-duty service. The strong bead and shoulder area ensure high puncture resistance as well as a longer tire life-cycle. As a result, you can deal with the most difficult operating conditions in a forest without concern.

UM

International Standard

Construction

 BIAS

Machinery

Agriculture: Forwarder

Version	STEEL BELTED
Type	TL
Tyre Size	710/40 - 22.5
LI/SS	161 A8/ 165 A2

Dimensions International Standard

Ply Rating	20
Section Width (mm)	710
Overall Diameter (mm)	1165
Static Loaded Radius (mm)	550
Rolling Circumference (mm)	3612
Rim Rec	AG 24.00
ECE	E11-106R-005273
TRA Code	LS2

Load capacity (Kg)

km/h / bar	5.0
40	4625
30	5000
10	5150

Printed on 20/04/2024 16:42

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..