

## FORESTECH - Technical Specifications



### Description

FORESTECH is a BKT bias steel-belted tire, suitable for forestry applications with forwarders. It provides excellent traction even in heavy-duty service. The strong bead and shoulder area ensure high puncture resistance as well as a longer tire life-cycle. As a result, you can deal with the most difficult operating conditions in a forest without concern.

### UM

International Standard

### Construction

 BIAS

### Machinery

Agriculture: Forwarder

Version	STEEL BELTED
Type	TL
Tyre Size	750/55 - 26.5
LI/SS	177 A8/184 A2

## Dimensions International Standard

<b>Ply Rating</b>	20
<b>Section Width (mm)</b>	755
<b>Overall Diameter (mm)</b>	1485
<b>Static Loaded Radius (mm)</b>	680
<b>Rolling Circumference (mm)</b>	4467
<b>Rim Rec</b>	AG 24.00
<b>ECE</b>	E11-106R-003347
<b>TRA Code</b>	LS2

## Load capacity (Kg)

	km/h / bar	5.00
	40	7300
	30	7810
	10	9000

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.

Printed on 13/05/2025 15:33

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..